

155-17801



Article Number: 155-17801

Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .02"- .12", PA66HIRHS, Black, 500/pkg



Base Data

Local Order Number 155-17801

Type CTC10FT9

Color Black (BK)

Features and Benefits

- Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.
- Extended fir tree allows for a wide range of panel thicknesses.
- Fir tree design provides low insertion forces and high extraction forces.

For Convoluted Tubing IWS 8,5-13

Product Description Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

Fixation Method (FF) Fir Tree

Short Description Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .02"- .12", PA66HIRHS, Black, 500/pkg

Product Dimensions

Width W (imperial) 0.31 "

Width W (metric) 8.0 mm

Height H (imperial) 0.89 "

Height H (metric) 22.7 mm

Height H2 (imperial) 0.48 "

Height H2 (metric) 12.2 mm

Disc Diameter (imperial) 0.87 "

Disc Diameter (metric) 23.0 mm

Panel Thickness max. (imperial) 0.12 "

Panel Thickness max. (metric) 5.0 mm

Panel Thickness min. (imperial) 0.12 "

Panel Thickness min. (metric) 3.0 mm

Mounting Hole Diameter D (imperial) 0.34 -0.35 "

Mounting Hole Diameter D (metric) 8.7 - 9.0 mm

Mounting Hole Diameter D min 0.34 "

(imperial) **Mounting Hole Diameter D max**0.35 "
(imperial)

Nominal Diameter (imperial)0.39 "

Nominal Diameter (metric) 10.0 mm

Mounting Hole Diameter D max 9.0 mm

(metric) **Mounting Hole Diameter D min (metric)**8.7 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	6000 Pieces
Weight (Metric)	1.4 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes