

155-32602



Article Number: 155-32602

Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack



## Base Data

Local Order Number 155-32602

Type FT6LG.M.St.Aufn.II

Color Black (BK)

**Features and Benefits** Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges. HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Fixation Method (FF) Fir Tree

Short Description Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack

## Product Dimensions

Length of Fir Tree 11.1 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16 mm

Panel Thickness max. (imperial) 0.2 "

Panel Thickness max. (metric) 5.0 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.75 mm

Mounting Hole Diameter D (imperial) 0.26-0.28 "

Mounting Hole Diameter D (metric) 6.5 - 7.0 mm

Mounting Hole Diameter D min (imperial) 0.26 "

Mounting Hole Diameter D max 0.28 "

(imperial)

Mounting Hole Diameter D max 7.0 mm

(metric) 6.5 mm

Mounting Hole Diameter D min (metric)

## Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 15000 Pieces

Weight (Metric) 0.8 kg

## Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes