

156-00036

Article Number: 156-00036



HellermannTyton

Base Data

Local Order Number 156-00036
Type T50ROC1A
Color Black (BK)

Features and Benefits OmegaClips were designed as a product solution in response to a recurring problem: how to add cables to preassembled cable looms post-installation. What was a difficult challenge has been made less complex thanks to OmegaClips, and much easier to achieve. Clips with a variety of twist angles and even different loop directions for the tie provide the requisite flexibility for cable routing in virtually any application.

Additional cable tie dimensions are available for the OC1 and 2A. Two loop directions are available for selection. In the case of the CBTO series, cable ties up to 5 mm in diameter can be used.

Fixation Method (FF) Omega Clips
Identification Plate Position none

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs
Minimum Tensile Strength (N) 225 N
Length L (imperial) 7.9 "
Length L (metric) 202 mm
Attaches to Diameter (imperial) 0.16 " - 0.4 "
Width W (imperial) 0.181 "
Width W (metric) 4.6 mm
Bundle Diameter min (imperial) 0.16 "
Bundle Diameter min (metric) 4.0 mm
Bundle Diameter max (imperial) 1.8 "
Bundle Diameter max (metric) 45.0 mm
Thickness T (imperial) 0.05 "
Attaches to Diameter (metric) 4.0 - 10.0 mm
Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag
Package Quantity 500
Carton Quantity 3000 Pieces
Weight (Metric) 1.3 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS
PA66HS

Flammability UL94 HB

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes