

156-00067

Article Number: 156-00067

Heavy Duty Fir Tree Mount with Cable Tie, Panel Thickness 0.04" - 0.25", PA66HIRHSUV, Black, 100/pkg



Base Data

Local Order Number 156-00067

Type T120RFT9A

Color Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
 - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
 - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

Product Description HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Fir Tree Mount with Cable Tie, Panel Thickness 0.04" - 0.25", PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 120.0 lbs

Minimum Tensile Strength (N) 535.0 N

Length L (imperial) 15.0 "

Length L (metric) 380.0 mm

Length L2 (imperial) 0.9 "

Length L2 (metric) 22.6 mm

Width W (imperial) 0.3 "

Width W (metric) 7.6 mm

Width W2 (imperial) 0.8 "

Width W2 (metric) 20.3 mm

Height H (imperial) 0.07 "

Height H (metric) 1.8 mm

Height H2 (imperial) 0.35 "

Height H2 (metric) 9.0 mm

Bundle Diameter max (imperial) 4.0 "

Bundle Diameter max (metric) 100.0 mm

Disc Diameter (imperial) 0.85 "

Disc Diameter (metric) 21.6 mm

Panel Thickness max. (imperial) 0.25 "

Panel Thickness max. (metric) 6.5 mm

Panel Thickness min. (imperial) 0.04 "

Panel Thickness min. (metric) 1.0 mm

Mounting Hole Diameter D (metric) 8.7 - 9.2 mm

**Mounting Hole Diameter D min
(imperial)** 0.34 "

Mounting Hole Diameter D max0.36 "
(imperial)

Mounting Hole Diameter D max9.2 mm
(metric)8.7 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Material Cable Tie Polyamide 6.6 heat stabilized (PA66HS)

Material Edge Clip Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Flammability UL94 HB

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes