

156-00135

Article Number: 156-00135

Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg



Base Data

Local Order Number	156-00135
Type	T50SVCOC15-18
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Omega Clip can be turned 360 degrees allowing for orientation in any direction.</li><li>• Design allows quick and easy installation by hand without the need for tools.</li><li>• Multiple bundle diameters available for all different ranges of bundles.</li></ul>
Product Description	Omega Clip Cable Ties provide the opportunity to attach a wire or hose to an existing bundle. Offering a full range of orientations, the wire/hose can be orientated in any direction in relations to the main harness. The Omega Clip design is ideally suited for easing the application process on the production floor by allowing for an easy one-step snap fit of the harness assembly to the wire or hose
Fixation Method (FF)	Omega Clips
Identification Plate Position	none
Tie Closure	plastic pawl
Short Description	Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	222 N
Length L (imperial)	6.0 "
Length L (metric)	155 mm
Attaches to Diameter (imperial)	0.6 "- 0.71 "
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.08 "
Bundle Diameter min (metric)	2.0 mm
Bundle Diameter max (imperial)	1.4 "
Bundle Diameter max (metric)	35.0 mm
Diameter min. (imperial)	0.59 "
Diameter max. (imperial)	0.71 "
Thickness T (imperial)	0.05 "
Attaches to Diameter (metric)	15.0 - 18.0
Thickness T (Metric)	1.35 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

**Carton Quantity** 3000 Pieces

**Weight (Metric)** 3.08 kg

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HIRHS  
PA66HS

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes