

156-00272



Article Number: 156-00272

Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .98" - 1.2", PA66HS, Black, 250/pkg

 RoHS

Base Data

Local Order Number	156-00272
Type	T50SVCOC25-31
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Omega Clip can be turned 360 degrees allowing for orientation in any direction.• Design allows quick and easy installation by hand without the need for tools.• Multiple bundle diameters available for all different ranges of bundles.
Product Description	Omega Clip Cable Ties provide the opportunity to attach a wire or hose to an existing bundle. Offering a full range of orientations, the wire/hose can be orientated in any direction in relations to the main harness. The Omega Clip design is ideally suited for easing the application process on the production floor by allowing for an easy one-step snap fit of the harness assembly to the wire or hose
Fixation Method (FF)	Omega Clips
Identification Plate Position	none
Tie Closure	plastic pawl
Short Description	Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .98" - 1.2", PA66HS, Black, 250/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	222 N
Length L (imperial)	6.0 "
Length L (metric)	155 mm
Attaches to Diameter (imperial)	0.98 "-1.22 "
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.08 "
Bundle Diameter min (metric)	2.0 mm
Bundle Diameter max (imperial)	1.4 "
Bundle Diameter max (metric)	35.0 mm
Diameter min. (imperial)	0.98 "
Diameter max. (imperial)	1.2 "
Thickness T (imperial)	0.05 "
Attaches to Diameter (metric)	25.0 -31.0
Thickness T (Metric)	1.35 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	250

Carton Quantity 1000 Pieces

Weight (Metric) 5.35 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS
PA66HS

Flammability UL94 HB

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes