

156-00444

Article Number: 156-00444

Arrowhead Mount Tie with Seal, 50lbs., Bundle Max 2.0", PA66HIRHS, Natural, 500/bag



## Base Data

Local Order Number 156-00444

Type T50ROSAH6MDU

Color Natural (NA)

- Features and Benefits**
- The arrowhead design of this tie offers a positive, low insertion force and a high extraction force.
  - Tie features a foam rubber seal which provides additional protection against moisture, dirt and other impurities.

**Product Description** The Arrowhead Mount Tie with seal provides a strong extraction force while being able to seal holes with its foam rubber seal which helps prevent against dirt and other impurities. This is used in many markets such as automobiles, aircrafts, and washing machines.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Mount Tie with Seal, 50lbs., Bundle Max 2.0", PA66HIRHS, Natural, 500/bag

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 8.5 "

Length L (metric) 216.0 mm

Width W (imperial) 0.2 "

Width W (metric) 5.0 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

Disc Diameter (imperial) 0.63 "

Disc Diameter (metric) 16.0 mm

Panel Thickness max. (imperial) 0.08 "

Panel Thickness max. (metric) 2.1 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.8 mm

Mounting Hole Diameter D min (imperial) 0.248 "

Mounting Hole Diameter D max (imperial) 0.252 "

Mounting Hole Diameter D max (metric) 6.6 mm  
6.3 mm

Mounting Hole Diameter D min (metric)

## Logistics and Packaging

---

**Quantity per** bag  
**Package Quantity** 500  
**Carton Quantity** 3000

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
**Material Shortcut** PA66HIRHS  
**Flammability** UL94 HB  
**Operating Temperature** -40 °F to +230 °F (-40 °C to +110 °C)  
**ROHS Conformity** Yes