

156-00457

Article Number: 156-00457

Heavy Duty Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .24"-.28", PA46, Brown, 500/pkg



Base Data

Local Order Number	156-00457
Type	T50RFT7HD
Color	Brown (BN)
Features and Benefits	• Staggered fir tree branch design provides low insertion forces and high extraction forces. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Product Description	Heavy Duty fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie, and is ideal in heavy duty environments.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Heavy Duty Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .24"-.28", PA46, Brown, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225 N

Length L (imperial)	8.0 "
Length L (metric)	200.0 mm
Length L2 (imperial)	0.5 "
Length L2 (metric)	11.6 mm
Length L3 (imperial)	0.78 "
Length L3 (metric)	19.3 mm
Width W (imperial)	0.18 "
Width W (metric)	4.6 mm
Width W2 (imperial)	0.23 "
Width W2 (metric)	5.9 mm
Width W3 (imperial)	0.23 "
Width W3 (metric)	5.9 mm
Height H (imperial)	0.78 "
Height H (metric)	19.8 mm
Height H2 (imperial)	0.36 "
Height H2 (metric)	12.4 mm
Bundle Diameter min (imperial)	0.16 "

Bundle Diameter min (metric)	4.0 mm
Bundle Diameter max (imperial)	1.8 "
Bundle Diameter max (metric)	45.0 mm
Disc Diameter (imperial)	0.9 "
Disc Diameter (metric)	21.6 mm
Panel Thickness max. (imperial)	0.28 "
Panel Thickness max. (metric)	7.0 mm
Panel Thickness min. (imperial)	0.03 "
Panel Thickness min. (metric)	0.8 mm
Mounting Hole Diameter D (imperial)	0.24 - 0.28 "
Mounting Hole Diameter D min (imperial)	0.244 "
	Mounting Hole Diameter D max0.284 "
	(imperial)
	Mounting Hole Diameter D max7.2 mm
	(metric)
Mounting Hole Diameter D min (metric)	6.2 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	1000

Material and Specifications

Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Flammability	UL94 V2
Operating Temperature	+275 °F (+135 °C)
ROHS Conformity	Yes