

156-00557



Article Number: 156-00557

Cable Tie and Edge Clip, 50lb, 8.0" Long, EC24, Panel Thickness .12"-.24", PA66HS, Black, 500/bag



## Base Data

Local Order Number 156-00557

Type T50REC24

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
  - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
  - Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

**Product Description** The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

**Fixation Method (FF)** EdgeClip, sideways, assembled, 2 piece

**Identification Plate Position** none

**Variant** Inside Serrated

**Short Description** Cable Tie and Edge Clip, 50lb, 8.0" Long, EC24, Panel Thickness .12"-.24", PA66HS, Black, 500/bag

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 8.0 "

Length L (metric) 200.0 mm

Width W (imperial) 0.18 "

Height H (imperial) 0.05 "

Height H (metric) 1.2 mm

Height H2 (imperial) 0.57 "

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.0 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 45.0 mm

Panel Thickness max. (imperial) 0.24 "

Panel Thickness max. (metric) 6.00 mm

Panel Thickness min. (imperial) 0.12 "

Panel Thickness min. (metric) 3.00 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)  
Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

**Material Shortcut** PA66HS

**ROHS Conformity** Yes