

156-00564



Article Number: 156-00564

Cable Tie and Edge Clip, 50lb, 8.0" Long, EC4A, Panel Thickness .04"- .12", PP, Black, 500/bag

 RoHS

Base Data

Local Order Number	156-00564
Type	T50REC4A
Color	Black (BK)
Features and Benefits	• Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. • Two piece assembly allows the mount to slide along the strap ensuring proper orientation.
Product Description	The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.
Fixation Method (FF)	EdgeClip, top, assembled, 2 piece
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Short Description	Cable Tie and Edge Clip, 50lb, 8.0" Long, EC4A, Panel Thickness .04"- .12", PP, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	110 N
Length L (imperial)	8.0 "
Length L (metric)	200 mm
Length L2 (imperial)	0.55 "
Length L2 (metric)	14.0 mm
Width W (imperial)	0.18 "
Width W (metric)	4.6 mm
Width W2 (imperial)	0.45 "
Width W2 (metric)	11.5 mm
Height H (imperial)	0.05 "
Height H (metric)	1.2 mm
Height H2 (imperial)	0.43 "
Height H2 (metric)	10.8 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	4.0 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	45.0 mm
Panel Thickness max. (imperial)	0.12 "
Panel Thickness max. (metric)	3.0 mm

Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	1.0 mm
Thickness T (imperial)	0.05 "
Thickness T (Metric)	1.2 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	4000

Material and Specifications

Material	Polypropylene (PP) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PP PA66HIRHS
ROHS Conformity	Yes