

157-00017

Article Number: 157-00017

Fir Tree with Tie, 6.7" Length, Mounting Hole Diameter 0.27" - 0.28", PA66, Black, 100/pkg



Base Data

Local Order Number	157-00017
Type	OS170
Color	Black (BK)
Features and Benefits	• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Short Description	Fir Tree with Tie, 6.7" Length, Mounting Hole Diameter 0.27" - 0.28", PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	30.0 lbs
Minimum Tensile Strength (N)	147 N
Length L (imperial)	6.7 "
Length L2 (imperial)	0.6 "
Length L2 (metric)	15.5 mm
Width W (imperial)	0.21 "
Width W (metric)	5.3 mm
Width W2 (imperial)	0.3 "
Width W2 (metric)	7.5 mm
Bundle Diameter max (imperial)	1.2 "
Bundle Diameter max (metric)	30.0 mm
Disc Diameter (imperial)	0.63 "
Disc Diameter (metric)	16.0 mm
Panel Thickness max. (imperial)	0.18 "
Panel Thickness max. (metric)	4.50 mm
Mounting Hole Diameter D (imperial)	0.27 - 0.28 "
Thickness T (imperial)	0.055 "
Thickness T (Metric)	1.4 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	2500

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes