

157-00068

Article Number: 157-00068

Fir Tree with Tie, 6.7" Length, Mounting Hole Diameter 0.24" - 0.26", PA66, Grey, 500/pkg



Base Data

Local Order Number 157-00068

Type OS180FT7LH

Color Gray (GY)

Features and Benefits

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

Product Description Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Fir Tree with Tie, 6.7" Length, Mounting Hole Diameter 0.24" - 0.26", PA66, Grey, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Length L (imperial) 7.0 "

Length L (metric) 180.0 mm

Width W (imperial) 0.21 "

Width W (metric) 5.3 mm

Width W2 (metric) 16 mm

Height H (imperial) 0.7 "

Bundle Diameter min (metric) 1.6 mm

Panel Thickness max. (imperial) 0.18 "

Panel Thickness max. (metric) 4.5 mm

Panel Thickness min. (imperial) 0.03 "

Panel Thickness min. (metric) 0.6 mm

Mounting Hole Diameter D (imperial) 0.24 - 0.26 "

Mounting Hole Diameter D (metric) 6.5 - 7.0 mm
6.35 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 3000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
ROHS Conformity	Yes