

157-00105



Article Number: 157-00105

Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 1000/pkg



## Base Data

Local Order Number 157-00105

Type T50SOSB5-High-E-C-CC

Color Black (BK)

**Features and Benefits**

- Head allows for a .2" lateral adjustment on stud during installation.
- Quick and easy installation ideal for manufacturing environment.

**Product Description** Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 1000/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.6 "

Length L (metric) 167.0 mm

Width W (imperial) 0.2 "

Width W (metric) 5.0 mm

Bundle Diameter min (imperial) 0.04 "

Bundle Diameter min (metric) 1.0 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Stud Length Max (imperial) 0.56 "

Stud Length max (metric) 14.2 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 1000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes