

157-00108



Article Number: 157-00108

Fir Tree Push Mount, 6.3" Long, Panel Thicknesses .02"-.17", Black, PA66HS, 1000/pkg



Base Data

Local Order Number	157-00108
Type	T50SOSFT6E2
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Fir Tree Push Mount offers simple and easy to use method of bundling and fixing cable ties. • The design of the fir tree ensures a positive secure fixing into panels with thicknesses from 0.6mm to 4.2mm or threaded blind holes. • The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
Product Description	Fir Tree Push Tie designed for fixing cable harnesses. Their simplicity and ease of use make them an option for anywhere where secure and easy installation are needed.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Short Description	Fir Tree Push Mount, 6.3" Long, Panel Thicknesses .02"-.17", Black, PA66HS, 1000/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	40.0 lbs
Minimum Tensile Strength (N)	180 N
Length L (imperial)	6.3 "
Length L (metric)	160.0 mm
Length L2 (imperial)	0.35 "
Length L2 (metric)	8.9 mm
Width W (imperial)	0.18 "
Width W (metric)	4.6 mm
Bundle Diameter min (imperial)	0.04 "
Bundle Diameter min (metric)	1.0 mm
Bundle Diameter max (imperial)	1.4 "
Bundle Diameter max (metric)	35.0 mm
Disc Diameter (imperial)	0.63 "
Disc Diameter (metric)	16.0 mm
Panel Thickness max. (imperial)	0.17 "
Panel Thickness max. (metric)	4.2 mm
Panel Thickness min. (imperial)	0.02 "
Panel Thickness min. (metric)	0.6 mm
Mounting Hole Diameter D (imperial)	0.24 - 0.275 "

Mounting Hole Diameter D (metric) 6.3 - 7.0 mm

**Mounting Hole Diameter D min
(imperial)** 0.248 "

Mounting Hole Diameter D max0.275 "
(imperial)

Mounting Hole Diameter D max7.0 mm
(metric)6.3 mm

Mounting Hole Diameter D min (metric)

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes