

157-00120



Article Number: 157-00120

Off-Set Fir Tree Cable Tie, 9.0" Long, 50lbs, Mounting Diameter .30" - .33", PA66HIRHS, Grey, 500/pkg



Base Data

Local Order Number 157-00120

Type T50ROSFT8SO25A

Color Gray (GY)

- Features and Benefits**
- Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.
 - Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.
 - Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Product Description HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.
The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Off-Set Fir Tree Cable Tie, 9.0" Long, 50lbs, Mounting Diameter .30" - .33", PA66HIRHS, Grey, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 222.0 N

Length L (imperial) 9.0 "

Length L (metric) 230.0 mm

Height H (imperial) 0.9 "

Height H (metric) 22.3 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

Panel Thickness max. (imperial) 0.26 "

Panel Thickness max. (metric) 6.65 mm

Panel Thickness min. (imperial) 0.02 "

Panel Thickness min. (metric) 0.6 mm

Mounting Hole Diameter D (imperial) 0.3 "

Mounting Hole Diameter D (metric) 7.6 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut PA66HIRHS
Flammability UL94 V2
ROHS Conformity Yes