

157-00130



**Article Number:** 157-00130

**Off-Set Fir Tree Cable Tie, 8.5" Long, 50lbs, Mounting Diameter .24" - .26", PA66HIRHS, Grey, 500/pkg**



## Base Data

**Local Order Number** 157-00130

**Type** T50ROSFT6SO12.5A

**Color** Gray (GY)

- Features and Benefits**
- Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.
  - Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.
  - Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

**Product Description** HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.

The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Fixation Method (FF)** Fir Tree

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Short Description** Off-Set Fir Tree Cable Tie, 8.5" Long, 50lbs, Mounting Diameter .24" - .26", PA66HIRHS, Grey, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (imperial)** 50.0 lbs

**Minimum Tensile Strength (N)** 222.0 N

**Length L (imperial)** 8.5 "

**Length L (metric)** 215.5 mm

**Height H (imperial)** 0.9 "

**Height H (metric)** 22.1 mm

**Bundle Diameter min (imperial)** 0.06 "

**Bundle Diameter min (metric)** 1.6 mm

**Bundle Diameter max (imperial)** 2.0 "

**Bundle Diameter max (metric)** 50.0 mm

**Panel Thickness max. (imperial)** 0.26 "

**Panel Thickness max. (metric)** 6.65 mm

**Panel Thickness min. (imperial)** 0.02 "

**Panel Thickness min. (metric)** 0.6 mm

**Mounting Hole Diameter D (imperial)** 0.2-0.27 "

## Logistics and Packaging

**Quantity per** bag

**Package Quantity** 500

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 V2
<b>ROHS Conformity</b>	Yes