

157-00142



**Article Number: 157-00142**

**Cable Tie 8" with Oval Fir Tree,PA66HIRHS, Black, 5000/CTN**



## Base Data

|                                      |  |
|--------------------------------------|--|
| <b>Local Order Number</b>            | 157-00142  |
| <b>Type</b>                          | T50ROSFTOVALU  |
| <b>Color</b>                         | Black (BK)   |
| <b>Features and Benefits</b>         | <ul style="list-style-type: none"> <li>• The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit into the hole.</li> <li>• The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</li> <li>• The oval hole fir tree fits 4 common automotive oval hole sizes.</li> </ul>  |
| <b>Product Description</b>           | <p>The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, the innovative design of the fir tree creates an interface with four different size holes that are commone in the automotive industry. The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit into the hole.</p> <p>The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</p> |
| <b>Fixation Method (FF)</b>          | Fir Tree for oval holes  |
| <b>Identification Plate Position</b> | none   |
| <b>Releasable Closure (Yes/No)</b>   | No   |
| <b>Tie Closure</b>                   | plastic pawl   |
| <b>Short Description</b>             | Cable Tie 8" with Oval Fir Tree,PA66HIRHS, Black, 5000/CTN   |

## Product Dimensions

|  |   |
|--|---|
| <b>Minimum Tensile Strength (imperial)</b> | 50.0 lbs  |
| <b>Minimum Tensile Strength (N)</b>        | 222.0 N   |
| <b>Length L (imperial)</b>                 | 8.0 "   |
| <b>Length L (metric)</b>                   | 225.0 mm  |
| <b>Bundle Diameter min (imperial)</b>      | 0.07 "  |
| <b>Bundle Diameter min (metric)</b>        | 1.8 mm  |
| <b>Bundle Diameter max (imperial)</b>      | 2.0 "   |
| <b>Bundle Diameter max (metric)</b>        | 50.0 mm   |
| <b>Panel Thickness max. (imperial)</b>     | 0.2 "   |
| <b>Panel Thickness max. (metric)</b>       | 6.75 mm   |
| <b>Panel Thickness min. (imperial)</b>     | 0.02 "  |
| <b>Panel Thickness min. (metric)</b>       | 0.6 mm  |
| <b>Mounting Hole Diameter D (imperial)</b> | 0.24 x 0.48 "; 0.25 x 0.50 ", 0.25 x 0.5 " ;0.27 x 0.47 " |

## Logistics and Packaging

|                         |     |
|-------------------------|-----|
| <b>Quantity per</b>     | bag |
| <b>Package Quantity</b> | 500 |

## Material and Specifications

---

|                          |   |
|--------------------------|---|
| <b>Material</b>          | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) |
| <b>Material Shortcut</b> | PA66HIRHS   |
| <b>ROHS Conformity</b>   | Yes   |