

157-00158

Article Number: 157-00158

Offset Fir tree, 25 mm, FT6, 8" Tie, 50lb Tensile Strength, PA46, Brown, 500/bag



## Base Data

Local Order Number 157-00158

Type T50ROSFT6SO25A

Color Brown (BN)

- Features and Benefits**
- One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.
  - The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.
  - The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Product Description** HellermannTyton's offset fir tree cable tie family creates an offset routing solution for our customers who are moving away from using tape. The offset branch creates a strong offset that reduces flexing and shifting of the bundle.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Offset Fir tree, 25 mm, FT6, 8" Tie, 50lb Tensile Strength, PA46, Brown, 500/bag

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 222.0 N

Length L (imperial) 9.0 "

Length L (metric) 230.0 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 1.96 "

Bundle Diameter max (metric) 50.0 mm

Panel Thickness max. (imperial) 0.3 "

Panel Thickness max. (metric) 6.65 mm

Panel Thickness min. (imperial) 0.02 "

Panel Thickness min. (metric) 0.6 mm

Mounting Hole Diameter D (imperial) 0.2-0.27 "

Mounting Hole Diameter D (metric) 6.1-7.0 mm

## Logistics and Packaging

Quantity per box

Package Quantity 500

## Material and Specifications

---

**Material** Polyamide 4.6 (PA46)

**Material Shortcut** PA46

**ROHS Conformity** Yes