

Article Number: 157-00164

One Piece Cable Tie w/Fir Tree, 25mm Offset at 90°angle, 6.5mm hole dia, 0.6-6.65mm Panel Thickness, PA66HIRHS, Black, 500/Pkg



Base Data

Local Order Number	157-00164
Type	T50ROSFT6SO25R
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• 25mm offset cable tie allows for the wire harness to be routed offset from the mounting surface with a cable tie solution versus bundling clips which have the ability to flex.• Offset bar creates additional strength with it's robust design to minimize potential flexing and shifting of the harness.• 90 Degree design allows for the bundle to sit securely underneath the offset bar and fir tree.
Product Description	HellermannTyton's 90 Degree Offset Cable tie offers a robust alternative to bundling clips, when needing to route a harness offset from the mounting surface. This fir tree cable tie lends itself to various panel thicknesses within the automotive industry.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Short Description	One Piece Cable Tie w/Fir Tree, 25mm Offset at 90°angle, 6.5mm hole dia, 0.6-6.65mm Panel Thickness, PA66HIRHS, Black, 500/Pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225.0 N
Length L (imperial)	9.3 "
Length L (metric)	237.0 mm
Bundle Diameter max (imperial)	1.9 "
Bundle Diameter max (metric)	50.0 mm
Panel Thickness max. (imperial)	0.26 "
Panel Thickness max. (metric)	6.65 mm
Panel Thickness min. (imperial)	0.02 "
Panel Thickness min. (metric)	0.6 mm
Mounting Hole Diameter D min (imperial)	0.24 "
Mounting Hole Diameter D max (imperial)	0.27 "
Mounting Hole Diameter D min (metric)	6.1 mm
Mounting Hole Diameter D max (metric)	7.0 mm

Logistics and Packaging

Quantity per box

Package Quantity 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

ROHS Conformity Yes