

157-00400



Article Number: 157-00400

Wide Strap Cable Tie, 1/4" Stud Mount, 9.7" Length, 0.5" Width, PA66HIRHSUV, Black, 300/pkg



## Base Data

Local Order Number 157-00400

Type WSS250

Color Black (BK)

- Features and Benefits**
- Mount provides low insertion and high extraction forces which makes for a strong and easy installation.
  - Clamping rails increase grip on round bundles.
  - Thinner strap provides increased flexibility for improved ergonomics.
  - Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

**Product Description** Wide Strap Heavy Duty Cable Ties features a stud mount for direct application onto an 1/4" threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 2.3". The low profile mount design engages a minimum of 4 threads on the stud, which makes it easier to apply additional mounts onto one stud.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Wide Strap Cable Tie, 1/4" Stud Mount, 9.7" Length, 0.5" Width, PA66HIRHSUV, Black, 300/pkg

## Product Dimensions

Minimum Tensile Strength (imperial) 120.0 lbs

Minimum Tensile Strength (N) 534 N

Length L (imperial) 9.7 "

Length L (metric) 236 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Bundle Diameter min (imperial) 0.38 "

Bundle Diameter min (metric) 10.0 mm

Bundle Diameter max (imperial) 2.3 "

Bundle Diameter max (metric) 57.0 mm

Stud Size (Imperial) 0.25 "

Stud Size (Metric) 6.35 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 300

Carton Quantity 1200

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-65 °F to +212 °F (-54 °C to +100 °C)
<b>ROHS Conformity</b>	Yes