

157-00401



Article Number: 157-00401

Wide Strap Tie with 0.25" Stud Mnt, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg



Base Data

Local Order Number	157-00401
Type	WSI250
Color	Black (BK)
Features and Benefits	• Applies to threaded studs for quick and easy installation. • Design of strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses. • Strap is flexible and utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.
Product Description	The Wide Strap Heavy Duty Cable Tie features a stud mount for direct application onto a 1/4" threaded stud. The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. A thinner strap provides increased flexibility for improved ergonomics.
Fixation Method (FF)	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Wide Strap Tie with 0.25" Stud Mnt, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	120.0 lbs
Minimum Tensile Strength (N)	534 N
Length L (imperial)	12.7 "
Length L (metric)	322.6 mm
Width W (imperial)	0.5 "
Width W (metric)	12.7 mm
Bundle Diameter min (imperial)	0.38 "
Bundle Diameter min (metric)	9.5 mm
Bundle Diameter max (imperial)	3.3 "
Bundle Diameter max (metric)	82.5 mm
Stud Size (Imperial)	0.25 "
Stud Size (Metric)	6.35 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	300
Carton Quantity	1200 Pieces

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes