

157-00404



Article Number: 157-00404

Wide Strap Tie with 0.38" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg



## Base Data

Local Order Number 157-00404

Type WSI380

Color Black (BK)

- Features and Benefits**
- Applies to threaded studs for quick and easy installation.
  - Design of strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses.
  - Strap is flexible and utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

**Product Description** The Wide Strap Heavy Duty Cable Tie features a stud mount for direct application onto a 3/8" threaded stud. The design of the strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses. The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. A thinner strap provides increased flexibility for improved ergonomics.

**Fixation Method (FF)** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Wide Strap Tie with 0.38" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg

## Product Dimensions

**Minimum Tensile Strength (imperial)** 120.0 lbs

**Minimum Tensile Strength (N)** 534 N

**Length L (imperial)** 12.7 "

**Length L (metric)** 322.6 mm

**Width W (imperial)** 0.5 "

**Width W (metric)** 12.7 mm

**Bundle Diameter min (imperial)** 0.38 "

**Bundle Diameter min (metric)** 9.5 mm

**Bundle Diameter max (imperial)** 3.3 "

**Bundle Diameter max (metric)** 82.5 mm

**Stud Size (Imperial)** 0.375 "

**Stud Size (Metric)** 9.52 mm

## Logistics and Packaging

**Quantity per** bag

**Package Quantity** 300

**Carton Quantity** 1200

**Weight (Metric)** 7.22 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +230 °F (-40 °C to +110 °C)
<b>ROHS Conformity</b>	Yes