

161-63403



Article Number: 161-63403

Helawrap HWPAV025 Flame Retardant Sleeve, 1.0" Dia., Polyamide 6V0, Black, 100.0 ft/Reel

 RoHS

Base Data

Local Order Number	161-63403
Type	HWPAV025
Color	Black (BK)
Features and Benefits	• Helawrap HWPAV0 can be applied rapidly and effortlessly with the handy applicator tool. • Helawrap HWPAV0 gives quick and easy access to cables and wires for inspection, maintenance and assembly at any time. • The special profile allows the easy application and removal from Helawrap HWPAV0. • Helawrap HWPAV0 is manufactured from halogen free flame-retardant PA6 (UL94 V0) and offers superior impact strength.
Product Description	The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.
Variant	Spiral Binding
Short Description	Helawrap HWPAV025 Flame Retardant Sleeve, 1.0" Dia., Polyamide 6V0, Black, 100.0 ft/Reel

Product Dimensions

Bundle Diameter min (imperial)	0.91 "
Bundle Diameter min (metric)	23 mm
Bundle Diameter max (imperial)	1.06 "
Bundle Diameter max (metric)	27 mm
Diameter D (imperial)	1.0 "
Diameter D (metric)	24.0 mm
Nominal Diameter (imperial)	1.0 "
Nominal Diameter (metric)	25 mm
Wall Thickness WT (imperial)	0.041 "
Wall Thickness WT (metric)	1.05 mm
Pitch (imperial)	0.79 "
Pitch (metric)	20 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	100 ft
Package Quantity	30 m
Reel Length (metric)	30 m
Reel Length (imperial)	100.0 ft
Weight (imperial)	8.06 lbs

Weight (Metric) 3.66 kg

Material and Specifications

Material	Polyamide 6 V0 (PA6V0)
Material Shortcut	PA6V0
Flammability	UL94 V0
Halogenfree	Yes
Operating Temperature	-40 °F to +194 °F (-40 °C to +90 °C)
ROHS Conformity	Yes
Certification / Specification	CEN TS 45545-2: 2009
UL Recognized (US)	Yes