



166-90104



**Article Number:** 166-90104

**HelaGuard Non Metallic IP66 Fitting, Straight, NPT Thread, 0.50" Dia., PA66, Black, 10/pkg**

 **RoHS**

Base Data

Local Order Number	166-90104
Type	HG050-S-0500
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• External NPT thread provides a secure connection.</li><li>• Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.</li><li>• All-around "teeth" attach firmly to conduit and deliver a high extraction force.</li><li>• Durable nylon material has high resistance to salts, oils, weak acids and solvents.</li><li>• IP66 fitting has one-piece construction.</li><li>• IP68 fitting has additional conduit seal for increased protection against wind, dirt and water.</li></ul>
Product Description	Straight fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. Choose from IP66 or IP68 ingress protection rated fittings.
Thread Type	NPT
Type of Connection	snap-connection
Variant	Straight
Short Description	HelaGuard Non Metallic IP66 Fitting, Straight, NPT Thread, 0.50" Dia., PA66, Black, 10/pkg

Product Dimensions

Length L (imperial)	1.73 "
Length L (metric)	44 mm
Bore Diameter (Imperial)	0.57 "
Bore Diameter (Metric)	14.5 mm
Clearance Hole Diameter (Imperial)	1.109 "
Clearance Hole Diameter (Metric)	28.17 mm
Euro (NW) Size	17 mm
Thread Length (Imperial)	0.55 "
Outside Diameter D (imperial)	1.26 "
Outside Diameter D (metric)	32 mm
Nominal Diameter (imperial)	1/2 "
Nominal Diameter (metric)	21 mm
Thread Length (metric)	14 mm

Logistics and Packaging

Quantity per	bag
Package Quantity (imperial)	10
Package Quantity	10 Pieces
Trade Size	1/2

Material and Specifications

---

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-58°F to +275°F (-50°C to +135°C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Listed (US)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes