# HellermannTyton

# 166-90105



Article Number: 166-90105

HelaGuard Non Metallic IP66 Fitting, Straight, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg

# RoHS

#### Base Data

166-90105
HG075-S-0750
Black (BK)
<ul> <li>External NPT thread provides a secure connection.</li> <li>Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.</li> <li>All-around "teeth" attach firmly to conduit and deliver a high extraction force.</li> <li>Durable nylon material has high resistance to salts, oils, weak acids and solvents.</li> <li>IP66 fitting has one-piece construction.</li> <li>IP68 fitting has additional conduit seal for increased protection against wind, dirt and water.</li> </ul>
Straight fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. Choose from IP66 or IP68 ingress protection rated fittings.
NPT
snap-connection
Straight
HelaGuard Non Metallic IP66 Fitting, Straight, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg

### **Product Dimensions**

Length L (imperial)	1.93 "
Length L (metric)	49 mm
Bore Diameter (Imperial)	0.76 "
Bore Diameter (Metric)	19.3 mm
Clearance Hole Diameter (Imperial)	1.375 "
Clearance Hole Diameter (Metric)	34.93 mm
Euro (NW) Size	23 mm
Thread Length (Imperial)	0.59 "
Outside Diameter D (imperial)	1.73 "
Outside Diameter D (metric)	44 mm
Nominal Diameter (imperial)	3/4 "
Nominal Diameter (metric)	28 mm
Thread Length (metric)	15 mm

## Logistics and Packaging

Quantity per	bag
Package Quantity (imperial)	10
Package Quantity	10 Pieces
Trade Size	3/4

#### **Material and Specifications**

Polyamide 6.6 (PA66)
PA66
UL94 V2
Yes
-58°F to +275°F (-50°C to +135°C)
Yes
No
No
Yes
Yes

© HellermannTyton 2014

UL