

166-90128

Article Number: 166-90128

HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.38" Dia., PA66, Black, 10/pkg



## Base Data

Local Order Number 166-90128

Type PSR038-90-0500

Color Black (BK)

- Features and Benefits**
- External NPT thread provides a secure connection.
  - Twist on installation makes future access fast and easy.
  - Internal spigot design helps ease threading of fitting onto conduit.
  - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
  - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
  - IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

**Product Description** Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.

**Short Description** HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.38" Dia., PA66, Black, 10/pkg

## Product Dimensions

Length L (imperial) 2.01 "

Length L (metric) 51 mm

Bore Diameter (Imperial) 0.41 "

Bore Diameter (Metric) 10.5 mm

Clearance Hole Diameter (Imperial) 0.875 "

Clearance Hole Diameter (Metric) 22.23 mm

Thread Length (Imperial) 0.51 "

Outside Diameter D (imperial) 1.10 "

Outside Diameter D (metric) 28 mm

Nominal Diameter (imperial) 3/8 "

Nominal Diameter (metric) 16 mm

Thread Length (metric) 13 mm

## Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 10

Package Quantity 10 Pieces

Trade Size 3/8

## Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +248°F (-40°C to +120°C)

**ROHS Conformity** Yes

**UL Listed (US and Canada)** No

**UL Listed (US)** No

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes