

166-90130

Article Number: 166-90130

HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg



## Base Data

Local Order Number 166-90130

Type PSR075-90-0750

Color Black (BK)

- Features and Benefits**
- External NPT thread provides a secure connection.
  - Twist on installation makes future access fast and easy.
  - Internal spigot design helps ease threading of fitting onto conduit.
  - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
  - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
  - IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

**Product Description** Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.

**Short Description** HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg

## Product Dimensions

Length L (imperial) 2.48 "

Length L (metric) 63 mm

Bore Diameter (Imperial) 0.75 "

Bore Diameter (Metric) 19 mm

Clearance Hole Diameter (Imperial) 1.375 "

Clearance Hole Diameter (Metric) 34.93 mm

Thread Length (Imperial) 0.59 "

Outside Diameter D (imperial) 1.65 "

Outside Diameter D (metric) 42 mm

Nominal Diameter (imperial) 3/4 "

Nominal Diameter (metric) 25 mm

Thread Length (metric) 15 mm

## Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 10

Package Quantity 10 Pieces

Trade Size 3/4

## Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +248°F (-40°C to +120°C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Listed (US)</b>	No
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes