

166-90132



Article Number: 166-90132

HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 1.25" Dia., PA66, Black, 2/pkg



Base Data

Local Order Number 166-90132

Type PSR125-90-1250

Color Black (BK)

- Features and Benefits**
- External NPT thread provides a secure connection.
 - Twist on installation makes future access fast and easy.
 - Internal spigot design helps ease threading of fitting onto conduit.
 - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
 - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
 - IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

Product Description Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.

Short Description HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 1.25" Dia., PA66, Black, 2/pkg

Product Dimensions

Length L (imperial) 4.45 "

Length L (metric) 113 mm

Bore Diameter (Imperial) 1.30 "

Bore Diameter (Metric) 33 mm

Clearance Hole Diameter (Imperial) 1.984 "

Clearance Hole Diameter (Metric) 50.39 mm

Thread Length (Imperial) 0.63 "

Outside Diameter D (imperial) 2.36 "

Outside Diameter D (metric) 60 mm

Nominal Diameter (imperial) 1-1/4 "

Nominal Diameter (metric) 40 mm

Thread Length (metric) 16 mm

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 2

Package Quantity 2 Pieces

Trade Size 1-1/4

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2
Operating Temperature -40°F to +248°F (-40°C to +120°C)
ROHS Conformity Yes
UL Listed (US and Canada) No
UL Listed (US) No
UL Recognized (US) Yes
UL Recognized (US and Canada) Yes