

166-90135

Article Number: 166-90135

HelaGuard Non Metallic IP65 Compression Fitting, Straight, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg



Base Data

Local Order Number 166-90135

Type PSR075-S-0750

Color Black (BK)

- Features and Benefits**
- External NPT thread provides a secure connection.
 - Twist on installation makes future access fast and easy.
 - Internal spigot design helps ease threading of fitting onto conduit.
 - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
 - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
 - IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

Product Description Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.

Short Description HelaGuard Non Metallic IP65 Compression Fitting, Straight, NPT Thread, 0.75" Dia., PA66, Black, 10/pkg

Product Dimensions

Length L (imperial) 1.77 "

Length L (metric) 45 mm

Bore Diameter (Imperial) 0.75 "

Bore Diameter (Metric) 19 mm

Clearance Hole Diameter (Imperial) 1.375 "

Clearance Hole Diameter (Metric) 34.93 mm

Thread Length (Imperial) 0.59 "

Outside Diameter D (imperial) 1.65 "

Outside Diameter D (metric) 42 mm

Nominal Diameter (imperial) 3/4 "

Nominal Diameter (metric) 25 mm

Thread Length (metric) 15 mm

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 10

Package Quantity 10 Pieces

Trade Size 3/4

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +248°F (-40°C to +120°C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US and Canada) Yes

UL Recognized (US) Yes