

166-90136



Article Number: 166-90136

HelaGuard Non Metallic IP65 Compression Fitting, Straight, NPT Thread, 1.00" Dia., PA66, Black, 10/pkg

 RoHS

Base Data	
Local Order Number	166-90136
Type	PSR100-S-1000
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• External NPT thread provides a secure connection.• Twist on installation makes future access fast and easy.• Internal spigot design helps ease threading of fitting onto conduit.• All-around "teeth" attach firmly to conduit and deliver a high extraction force.• Durable nylon material has high resistance to salts, oils, weak acids and solvents.• IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.
Product Description	Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.
Short Description	HelaGuard Non Metallic IP65 Compression Fitting, Straight, NPT Thread, 1.00" Dia., PA66, Black, 10/pkg

Product Dimensions	
Length L (imperial)	1.89 "
Length L (metric)	48 mm
Bore Diameter (Imperial)	0.97 "
Bore Diameter (Metric)	24.5 mm
Clearance Hole Diameter (Imperial)	1.734 "
Clearance Hole Diameter (Metric)	44.04 mm
Thread Length (Imperial)	0.63 "
Outside Diameter D (imperial)	1.89 "
Outside Diameter D (metric)	48 mm
Nominal Diameter (imperial)	1 "
Nominal Diameter (metric)	32 mm
Thread Length (metric)	16 mm

Logistics and Packaging	
Quantity per	bag
Package Quantity (imperial)	10
Package Quantity	10 Pieces
Trade Size	1

Material and Specifications	
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66

Flammability	UL94 V2
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Listed (US)	No
UL Recognized (US and Canada)	Yes
UL Recognized (US)	Yes