

166-90175



Article Number: 166-90175

HelaGuard Non Metallic IP66 Fitting, T-Connector, 0.75" Dia., PA66, Black, 3/pkg



Base Data

Local Order Number 166-90175

Type HG075-T

Color Black (BK)

- Features and Benefits**
- Used to join conduits of same diameters and route to multiple directions.
 - Inspection lid facilitates cable pull through and eases installation.
 - Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
 - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
 - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
 - Vibration and shock tested to EN61373 Category 2.
 - IP66 fitting has one-piece construction.
 - IP68 fitting has additional conduit seal for increased protection against wind, dirt and water.

Product Description T-Connectors are used to join three same diameter corrugated conduits together, and redirect cables into multiple directions. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. Choose from IP66 or IP68 ingress protection rated fittings.

Type of Connection snap-connection

Variant T-Connector

Short Description HelaGuard Non Metallic IP66 Fitting, T-Connector, 0.75" Dia., PA66, Black, 3/pkg

Product Dimensions

Length L (imperial) 3.42 "

Length L (metric) 87 mm

Bore Diameter (Imperial) 0.98 "

Bore Diameter (Metric) 25 mm

Euro (NW) Size 23 mm

Outside Diameter D (imperial) 4.92 "

Outside Diameter D (metric) 125 mm

Nominal Diameter (imperial) 3/4 "

Nominal Diameter (metric) 28 mm

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 3

Package Quantity 3 Pieces

Trade Size 3/4

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -58°F to +275°F (-50°C to +135°C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US and Canada) Yes

UL Recognized (US) Yes