


166-90203



Article Number: 166-90203

HelaGuard Non Metallic Conduit, Flame Retardant, Std. Weight, 0.50" Dia., Nylon PA6-FR, Black, 100.0 ft/Std. Reel

 RoHS

Base Data

Local Order Number	166-90203
Type	HG-FR0500
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Flame retardant material; meets low flammability, smoke and toxicity ratings.</li><li>• Easy to use and cut; reduces installation time and labor costs.</li><li>• Flexible, abrasion resistant and durable for a variety of applications.</li><li>• Good impact strength; recovers quickly if crushed.</li><li>• Rated UL94 V0.</li><li>• UV resistant; suitable for use in outdoor applications.</li><li>• Offered in fine or course corrugated pitch.</li></ul>
Product Description	A standard weight corrugated conduit made of a flame retardant material for use in applications in which high fire protection and low flammability are primary requirements. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard Non-Metallic Fittings for IP66 rating or greater protection against water, wind and dirt.
Pitch Type	F (Fine)
Short Description	HelaGuard Non Metallic Conduit, Flame Retardant, Std. Weight, 0.50" Dia., Nylon PA6-FR, Black, 100.0 ft/Std. Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.5 m
Inner Diameter D (Imperial)	0.66 "
Inner Diameter D (metric)	16.7 mm
Euro (NW) Size	17 mm
Outside Diameter D (imperial)	0.84 "
Outside Diameter D (metric)	21.2 mm
Nominal Diameter (imperial)	1/2 "
Nominal Diameter (metric)	21 mm
Inside Bend Radius (Imperial)	1.78 "
Inside Bend Radius (Metric)	45 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	30.5 m
Trade Size	1/2

Material and Specifications

Material	Polyamide 6, Flame retardant (PA6-FR)
----------	---------------------------------------

<b>Material Shortcut</b>	PA6-FR
<b>Flammability</b>	UL94 V0
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +248°F (-40°C to +120°C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US)</b>	No
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Recognized (US)</b>	Yes