HellermannTyton

166-90223



Article Number: 166-90223

HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.00" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel

RoHS

Base Data

Local Order Number 166-90223

Type PSR1000 Color Black (BK)

Features and Benefits • Spiral reinforced construction provides protection from crushing yet remains extremely flexible.

• Lightweight, easy-to-use material reduces installation time and labor costs.

· Material stands up to vibration and limited torsional movement without creation of stress points or cracks.

• Smooth inside bore protects wires and eases insertion of wire bundles.

• UV resistant; suitable for use in outdoor applications.

Product Description A lightweight tubing with a smooth inside bore, made of a spiral reinforced PVC material that provides high flexibility.

This tubing is well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with

HelaGuard Non-Metallic Compression Fittings to create an enclosed system.

Short Description

HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.00" Dia., Spiral Reinforced PVC Tubing, Black, 100.0

ft/Std. Reel

Product Dimensions

Length L (imperial) 100.0 ft

Length L (metric) 30.5 m

Inner Diameter D (Imperial) 1.11 "

Inner Diameter D (metric) 28 mm

Outside Diameter D (imperial) 1.32 "

Outside Diameter D (metric) 33.5 mm

Nominal Diameter (imperial) 1 "

Nominal Diameter (metric)

Inside Bend Radius (Imperial) 2.36 "

Inside Bend Radius (Metric) 60 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 100 ft

Package Quantity 30.5 m

Trade Size 1

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing according to EN IEC 61386

Halogenfree No

Operating Temperature $-4^{\circ}F$ to +158°F (-20°C to +70°C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US and Canada) Yes

UL Recognized (US) Yes