

166-90224



Article Number: 166-90224

HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.25" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel



Base Data

Local Order Number 166-90224

Type PSR1250

Color Black (BK)

- Features and Benefits**
- Spiral reinforced construction provides protection from crushing yet remains extremely flexible.
 - Lightweight, easy-to-use material reduces installation time and labor costs.
 - Material stands up to vibration and limited torsional movement without creation of stress points or cracks.
 - Smooth inside bore protects wires and eases insertion of wire bundles.
 - UV resistant; suitable for use in outdoor applications.

Product Description A lightweight tubing with a smooth inside bore, made of a spiral reinforced PVC material that provides high flexibility. This tubing is well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Non-Metallic Compression Fittings to create an enclosed system.

Short Description HelaGuard, Smooth Bore, Spiral Cover, Std. Weight, PVC 1.25" Dia., Spiral Reinforced PVC Tubing, Black, 100.0 ft/Std. Reel

Product Dimensions

Length L (imperial) 100.0 ft

Length L (metric) 30.5 m

Inner Diameter D (Imperial) 1.38 "

Inner Diameter D (metric) 35 mm

Outside Diameter D (imperial) 1.62 "

Outside Diameter D (metric) 41.0 mm

Nominal Diameter (imperial) 1-1/4 "

Nominal Diameter (metric) 40 mm

Inside Bend Radius (Imperial) 3.15 "

Inside Bend Radius (Metric) 80 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 100 ft

Package Quantity 30.5 m

Trade Size 1-1/4

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing according to EN IEC 61386

Halogenfree No

Operating Temperature -4°F to +158°F (-20°C to +70°C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes