



169-60019



Article Number: 169-60019

Convoluted Tubing, Slit, 0.5" Diameter, PA6, Black, 100ft/pkg

 **RoHS**

Base Data

Local Order Number	169-60019
Type	CTN120
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 0.5" Diameter, PA6, Black, 100ft/pkg

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Width W (imperial)	0.127 "
Diameter D (imperial)	0.7 "
Diameter D (metric)	17.78 mm
Diameter D2 (imperial)	0.516 "
Diameter D2 (metric)	13.11 mm
Nominal Diameter (imperial)	0.5 "
Nominal Diameter (metric)	12.7 mm
Wall Thickness WT (imperial)	0.005 "
Wall Thickness WT (metric)	0.127 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100.0 ft
Package Quantity	30.48 m

Material and Specifications

Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Operating Temperature	-40 °F to +300 °F (-40 °C to +149 °C)
ROHS Conformity	Yes

