

170-03010



Article Number: 170-03010

Flame Retardant Expandable Braided Sleeving, 1.25" Dia., Black, 50.0 ft/Standard Reel



Base Data

Local Order Number 170-03010

Type BSPFR1140

Color Black (BK)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Open Post Termination No

Short Description Flame Retardant Expandable Braided Sleeving, 1.25" Dia., Black, 50.0 ft/Standard Reel

Product Dimensions

Length L (imperial) 50.0 ft

Length L (metric) 15.2 m

Bundle Diameter min (imperial) 0.75 "

Bundle Diameter min (metric) 19.1 mm

Bundle Diameter max (imperial) 1.75 "

Bundle Diameter max (metric) 44.5 mm

Nominal Diameter (imperial) 1.25 "

Nominal Diameter (metric) 31.8 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 50 ft

Package Quantity 50.0 ft

Reel Length (imperial) 50.0 ft

Reel Length (metric) 15.2 m

Weight (imperial) 0.8 lbs

Weight (Metric) 0.363 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability Mil-202

FAR 25
FMVSS 302
VW-1

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes