

170-03012



Article Number: 170-03012

Fray Resistant Expandable Braided Sleeving, 0.5" Dia., PET, Black, 100.0 ft/Standard Reel



Base Data

Local Order Number 170-03012

Type BSPSC120

Color Black (BK)

Features and Benefits

- Cuts with scissors without fraying ends enables field installations without need for hot knife.
- Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.
- Expands to 150% of easy installation and reduced assembly time requirements.

Product Description A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors.

Open Post Termination No

Short Description Fray Resistant Expandable Braided Sleeving, 0.5" Dia., PET, Black, 100.0 ft/Standard Reel

Product Dimensions

Length L (imperial) 100.0 ft

Length L (metric) 30.48 m

Bundle Diameter min (imperial) 0.25 "

Bundle Diameter min (metric) 6.4 mm

Bundle Diameter max (imperial) 0.75 "

Bundle Diameter max (metric) 19.1 mm

Nominal Diameter (imperial) 0.5 "

Nominal Diameter (metric) 12.7 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 100 ft

Package Quantity 100.0 ft

Reel Length (metric) 30.5 m

Reel Length (imperial) 100.0 ft

Weight (imperial) 0.82 lbs

Weight (Metric) 0.37 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes