


170-03013



**Article Number:** 170-03013

**Fray Resistant Expandable Braided Sleeving, 0.75" Dia., PET, Black, 75.0 ft/Standard Reel**

 **RoHS**

Base Data

|                       |  |
|-----------------------|--|
| Local Order Number    | 170-03013  |
| Type                  | BSPSC340   |
| Color                 | Black (BK)   |
| Features and Benefits | <ul style="list-style-type: none"><li>• Cuts with scissors without fraying ends enables field installations without need for hot knife.</li><li>• Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.</li><li>• Expands to 150% of easy installation and reduced assembly time requirements.</li></ul> |
| Product Description   | A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors.  |
| Open Post Termination | No   |
| Short Description     | Fray Resistant Expandable Braided Sleeving, 0.75" Dia., PET, Black, 75.0 ft/Standard Reel  |

Product Dimensions

|                                |         |
|--------------------------------|---------|
| Length L (imperial)            | 75.0 ft |
| Length L (metric)              | 22.9 m  |
| Bundle Diameter min (imperial) | 0.625 " |
| Bundle Diameter min (metric)   | 15.9 mm |
| Bundle Diameter max (imperial) | 1.0 "   |
| Bundle Diameter max (metric)   | 25.4 mm |
| Nominal Diameter (imperial)    | 0.75 "  |
| Nominal Diameter (metric)      | 19.1 mm |

Logistics and Packaging

|                             |            |
|-----------------------------|------------|
| Quantity per                | reel       |
| Package Quantity (imperial) | 75 ft      |
| Package Quantity            | 75.0 ft    |
| Reel Length (metric)        | 22.9 m     |
| Reel Length (imperial)      | 75.0 ft    |
| Weight (imperial)           | 0.8325 lbs |
| Weight (Metric)             | 0.38 kg    |

Material and Specifications

|                   |                 |
|-------------------|-----------------|
| Material          | Polyester (PET) |
| Material Shortcut | PET             |
| Flammability      | UL94 V0         |
| Melting Point     | +250 °C         |

**Operating Temperature** -94 °F to +257 °F (-70 °C to +125 °C)

**ROHS Conformity** Yes

**UL Recognized (US and Canada)** Yes