

170-03026



Article Number: 170-03026

Split Wrap Braided Sleeving, 1.25" ID, PET, Black, 25.0 ft/Standard Reel



Base Data

Local Order Number 170-03026

Type BSPSW1140

Color Black (BK)

- Features and Benefits**
- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
 - Unique construction retains shape and rigidity throughout unrolling.
 - Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Product Description A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Split Wrap Braided Sleeving, 1.25" ID, PET, Black, 25.0 ft/Standard Reel

Product Dimensions

Length L (imperial) 25.0 ft

Length L (metric) 7.62 m

Bundle Diameter max (imperial) 1.25 "

Bundle Diameter max (metric) 31.8 mm

Nominal Diameter (imperial) 1.25 "

Nominal Diameter (metric) 31.8 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 25 ft

Package Quantity 25.0 ft

Weight (imperial) 0.6 lbs

Weight (Metric) 0.27 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

