

170-03051

Article Number: 170-03051

Resin Coated Fiberglass Sleeve, 0.5" Dia., Black, 200.0 ft/Bulk Reel



Base Data

Local Order Number 170-03051

Type BSHTFG120B

Color Black (BK)

- Features and Benefits**
- An extremely tough sleeving material which provides thermal protection up to 1,200°F.
 - Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
 - Cuts easily with ordinary scissors for easy application.
 - UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

Product Description An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.

Open Post Termination No

Short Description Resin Coated Fiberglass Sleeve, 0.5" Dia., Black, 200.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 200.0 ft

Length L (metric) 61.0 m

Bundle Diameter max (imperial) 0.75 "

Bundle Diameter max (metric) 19.1 mm

Nominal Diameter (imperial) 0.5 "

Nominal Diameter (metric) 12.7 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 200 ft

Package Quantity 200.0 ft

Reel Length (imperial) 200.0 ft

Reel Length (metric) 61.0 m

Weight (imperial) 9.6 lbs

Weight (Metric) 4.35 kg

Material and Specifications

Material Glass Fiber (GF)

Operating Temperature -94 °F to +1202 °F (-70 °C to +650 °C)

ROHS Conformity Yes

UL Recognized (US) Yes

