

170-03053



Article Number: 170-03053

Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 100.0 ft/Bulk Reel



Base Data

Local Order Number	170-03053
Type	BSHTFG100B
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• An extremely tough sleeving material which provides thermal protection up to 1,200°F.• Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.• Cuts easily with ordinary scissors for easy application.• UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.
Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
Open Post Termination	No
Short Description	Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 100.0 ft/Bulk Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Bundle Diameter max (imperial)	1.625 "
Bundle Diameter max (metric)	41.3 mm
Nominal Diameter (imperial)	1.0 "
Nominal Diameter (metric)	25.4 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Reel Length (imperial)	100.0 ft
Reel Length (metric)	30.5 m
Weight (imperial)	10.5 lbs
Weight (Metric)	4.76 kg

Material and Specifications

Material	Glass Fiber (GF)
Operating Temperature	-94 °F to +1202 °F (-70 °C to +650 °C)
ROHS Conformity	Yes
UL Recognized (US)	Yes

