

170-03055



Article Number: 170-03055

Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver, 250.0 ft/Bulk Reel



Base Data

Local Order Number 170-03055

Type BSHTTST34SRB

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
 - Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Open Post Termination No

Short Description Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver, 250.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 250.0 ft

Length L (metric) 76.2 m

Bundle Diameter max (imperial) 0.687 "

Bundle Diameter max (metric) 17.4 mm

Nominal Diameter (imperial) 0.75 "

Nominal Diameter (metric) 19.1 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 250 ft

Package Quantity 1 Reel

Reel Length (metric) 76.2 m

Reel Length (imperial) 250.0 ft

Weight (imperial) 8.625 lbs

Weight (Metric) 3.91 kg

Material and Specifications

Material Aluminium (AL)
Glass Fiber (GF)

Flammability non flammable

Melting Point +255 °C

Operating Temperature -76 °F to +491 °F (-60 °C to +255 °C)

ROHS Conformity Yes

