# HellermannTyton

## 170-03056



Article Number: 170-03056

Aluminum Laminated Fiberglass Sleeving Tube, 1.0" Dia., Silver, 250.0 ft/Bulk Reel

RoHS

### **Base Data**

Local Order Number 170-03056

Type BSHTTST10SRB

Color Silver (SR)

Features and Benefits • A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.

• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature

environments

· Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single

solution that is able to deflect radiant heat away from sensitive components inside the tube.

Open Post Termination No

Short Description Aluminum Laminated Fiberglass Sleeving Tube, 1.0" Dia., Silver, 250.0 ft/Bulk Reel

#### **Product Dimensions**

Length L (imperial) 250.0 ft

Length L (metric) 76.2 m

Bundle Diameter max (imperial) 0.937 "

Bundle Diameter max (metric) 23.8 mm

Nominal Diameter (imperial) 1.0 "

Nominal Diameter (metric) 25.4 mm

## **Logistics and Packaging**

Quantity per reel

Package Quantity (imperial) 250 ft

Package Quantity 1

Reel Length (metric) 76.2 m

Reel Length (imperial) 250.0 ft

Weight (imperial) 11.25 lbs

Weight (Metric) 5.08 kg

# **Material and Specifications**

Material Aluminium (AL)

Glass Fiber (GF)

Flammability non flammable

Melting Point +255 °C

Operating Temperature -76 °F to +491 °F (-60 °C to +255 °C)

ROHS Conformity Yes

© HellermannTyton 2014