

170-03057



Article Number: 170-03057

Aluminum Laminated Fiberglass Sleeve, 1.75" Dia., Silver, 100.0 ft/Bulk Reel

 RoHS

Base Data

|                       |  |
|-----------------------|--|
| Local Order Number    | 170-03057  |
| Type                  | BSHTTST134SRB  |
| Color                 | Silver (SR)  |
| Features and Benefits | <ul style="list-style-type: none"><li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li><li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li><li>• Cuts with ordinary scissors for fast, easy application.</li></ul> |
| Product Description   | A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.   |
| Open Post Termination | No   |
| Short Description     | Aluminum Laminated Fiberglass Sleeve, 1.75" Dia., Silver, 100.0 ft/Bulk Reel   |

Product Dimensions

|                                |          |
|--------------------------------|----------|
| Length L (imperial)            | 100.0 ft |
| Length L (metric)              | 30.48 m  |
| Bundle Diameter max (imperial) | 1.687 "  |
| Bundle Diameter max (metric)   | 42.8 mm  |
| Nominal Diameter (imperial)    | 1.75 "   |
| Nominal Diameter (metric)      | 44.5 mm  |

Logistics and Packaging

|                             |          |
|-----------------------------|----------|
| Quantity per                | reel     |
| Package Quantity (imperial) | 100 ft   |
| Package Quantity            | 1 Reel   |
| Reel Length (metric)        | 30.5 m   |
| Reel Length (imperial)      | 100.0 ft |
| Weight (imperial)           | 7.40 lbs |
| Weight (Metric)             | 3.36 kg  |

Material and Specifications

|                       |                                       |
|-----------------------|---------------------------------------|
| Material              | Glass Fiber (GF)<br>Aluminium (AL)    |
| Flammability          | non flammable                         |
| Melting Point         | +255 °C                               |
| Operating Temperature | -76 °F to +491 °F (-60 °C to +255 °C) |
| ROHS Conformity       | Yes                                   |

