


170-03058



Article Number: 170-03058

Resin Coated Fiberglass Sleeve, 0.25" Dia., Black, 50.0 ft/Standard Reel

 RoHS

Base Data

| | |
|-----------------------|--|
| Local Order Number | 170-03058 |
| Type | BSHTFG140 |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none">• An extremely tough sleeving material which provides thermal protection up to 1,200°F.• Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.• Cuts easily with ordinary scissors for easy application.• UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance. |
| Product Description | An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress. |
| Open Post Termination | No |
| Short Description | Resin Coated Fiberglass Sleeve, 0.25" Dia., Black, 50.0 ft/Standard Reel |

Product Dimensions

| | |
|--------------------------------|---------|
| Length L (imperial) | 50.0 ft |
| Length L (metric) | 15.2 m |
| Bundle Diameter max (imperial) | 0.375 " |
| Bundle Diameter max (metric) | 9.5 mm |
| Nominal Diameter (imperial) | 0.25 " |
| Nominal Diameter (metric) | 6.4 mm |

Logistics and Packaging

| | |
|-----------------------------|---------|
| Package Quantity (imperial) | 50 ft |
| Reel Length (imperial) | 50.0 ft |
| Reel Length (metric) | 15.2 m |
| Weight (imperial) | 1.0 lbs |
| Weight (Metric) | 0.45 kg |

Material and Specifications

| | |
|-----------------------|--|
| Material | Glass Fiber (GF) |
| Operating Temperature | -94 °F to +1202 °F (-70 °C to +650 °C) |
| ROHS Conformity | Yes |
| UL Recognized (US) | Yes |

