

170-03061



Article Number: 170-03061

Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 25.0 ft/Standard Reel

 RoHS

Base Data

Local Order Number	170-03061
Type	BSHTFG100
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• An extremely tough sleeveing material which provides thermal protection up to 1,200°F.• Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.• Cuts easily with ordinary scissors for easy application.• UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.
Product Description	An extremely high-temperature resistant sleeveing designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
Open Post Termination	No
Short Description	Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 25.0 ft/Standard Reel

Product Dimensions

Length L (imperial)	25.0 ft
Length L (metric)	7.62 m
Bundle Diameter max (imperial)	1.625 "
Bundle Diameter max (metric)	41.3 mm
Nominal Diameter (imperial)	1.0 "
Nominal Diameter (metric)	25.4 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	25 ft
Reel Length (imperial)	25.0 ft
Reel Length (metric)	7.6 m
Weight (imperial)	2.61 lbs
Weight (Metric)	1.2 kg

Material and Specifications

Material	Glass Fiber (GF)
Operating Temperature	-94 °F to +1202 °F (-70 °C to +650 °C)
ROHS Conformity	Yes
UL Recognized (US)	Yes

