

170-03064



Article Number: 170-03064

Aluminum Laminated Fiberglass Sleeve Tube, 1.0" Dia., Silver, 250.0 ft/Standard Reel

 RoHS

Base Data

Local Order Number	170-03064
Type	BSHTTST10SR
Color	Silver (SR)
Features and Benefits	<ul style="list-style-type: none">• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.• Cuts with ordinary scissors for fast, easy application.
Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
Open Post Termination	No
Short Description	Aluminum Laminated Fiberglass Sleeve Tube, 1.0" Dia., Silver, 250.0 ft/Standard Reel

Product Dimensions

Length L (imperial)	100.0 ft
Length L (metric)	30.48 m
Bundle Diameter max (imperial)	0.937 "
Bundle Diameter max (metric)	23.8 mm
Nominal Diameter (imperial)	1.0 "
Nominal Diameter (metric)	25.4 mm

Logistics and Packaging

Quantity per	reel
Package Quantity (imperial)	100 ft
Package Quantity	1
Reel Length (metric)	30.5 m
Reel Length (imperial)	100.0 ft
Weight (imperial)	4.50 lbs
Weight (Metric)	2.0 kg

Material and Specifications

Material	Aluminium (AL) Glass Fiber (GF)
Flammability	non flammable
Melting Point	+255 °C
Operating Temperature	-76 °F to +491 °F (-60 °C to +255 °C)
ROHS Conformity	Yes

