

170-03065



Article Number: 170-03065

Aluminum Laminated Fiberglass Sleeving, 1.75" Dia., Silver, 50.0 ft/Standard Reel



Base Data

Local Order Number 170-03065

Type BSHTTST134SR

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
 - Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Open Post Termination No

Short Description Aluminum Laminated Fiberglass Sleeving, 1.75" Dia., Silver, 50.0 ft/Standard Reel

Product Dimensions

Length L (imperial) 50.0 ft

Length L (metric) 15.2 m

Bundle Diameter max (imperial) 1.687 "

Bundle Diameter max (metric) 42.8 mm

Nominal Diameter (imperial) 1.75 "

Nominal Diameter (metric) 44.5 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 50 ft

Package Quantity 1

Reel Length (metric) 15.2 m

Reel Length (imperial) 50.0 ft

Weight (imperial) 3.70 lbs

Weight (Metric) 1.68 kg

Material and Specifications

Material Glass Fiber (GF)
Aluminium (AL)

Flammability non flammable

Melting Point +255 °C

Operating Temperature -76 °F to +491 °F (-60 °C to +255 °C)

ROHS Conformity Yes

