

170-03074



Article Number: 170-03074

Flame Retardant Expandable Braided Sleeving, 0.75" Dia., Gray, 75.0 ft/Standard Reel



Base Data

Local Order Number 170-03074

Type BSPFR348

Color Gray (GY)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Open Post Termination No

Short Description Flame Retardant Expandable Braided Sleeving, 0.75" Dia., Gray, 75.0 ft/Standard Reel

Product Dimensions

Length L (imperial) 75.0 ft

Length L (metric) 22.9 m

Bundle Diameter min (imperial) 0.5 "

Bundle Diameter min (metric) 12.7 mm

Bundle Diameter max (imperial) 1.25 "

Bundle Diameter max (metric) 31.8 mm

Nominal Diameter (imperial) 0.75 "

Nominal Diameter (metric) 19.1 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 75 ft

Package Quantity 75.0 ft

Reel Length (imperial) 75.0 ft

Reel Length (metric) 22.9 m

Weight (imperial) 0.65 lbs

Weight (Metric) 0.3 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability FMVSS 302

VW-1
FAR 25
Mil-202

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes