

170-03083



Article Number: 170-03083

Split Wrap Braided Sleeving, 0.5" ID, PET, Orange, 150.0 ft/Bulk Reel



Base Data

Local Order Number 170-03083

Type BSPSW123B

Color Orange (OG)

Features and Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Product Description A lateral split, semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Split Wrap Braided Sleeving, 0.5" ID, PET, Orange, 150.0 ft/Bulk Reel

Product Dimensions

Length L (imperial) 150.0 ft

Length L (metric) 45.7 m

Bundle Diameter max (imperial) 0.5 "

Bundle Diameter max (metric) 12.7 mm

Nominal Diameter (imperial) 0.5 "

Nominal Diameter (metric) 12.7 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 150 ft

Package Quantity 150.0 ft

Reel Length (metric) 45.7 m

Reel Length (imperial) 150.0 ft

Weight (imperial) 2.1

Weight (Metric) 0.95 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Melting Point +250 °C

Operating Temperature -94 °F to +257 °F (-70 °C to +125 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes